

Page: 1 of 7

This version issued: July, 2025

# **Section 1 - Identification of the Material and Supplier**

Candan Industries Pty. Ltd

Telephone: (07) 3209 8733

65 Chetwynd St

Fax: (07) 3209 8744

Loganholme QLD 4129 AUSTRALIA

Emergency Telephone number (A/HR) 0424 332 121

New Zealand Supplier: INOX New Zealand

In New Zealand: Emergency 0212 811 500

In New Zealand: Phone 0212 811 500, Fax 09 929 3177

Chemical nature: Resin coating dispensed by aerosol
Trade Name: INOX MX12 PTFE Supa Glide

**Product Code:** 00604 (175 g)

**Product Use:** Fast-drying resin, containing corrosion inhibitors, suitable for use on various surfaces.

Creation Date: December, 2016

This version issued: July, 2025 and is valid for 5 years from this date.

Poisons Information Centre: Phone 13 11 26 from anywhere in Australia

## **Section 2 - Hazards Identification**

### **Statement of Hazardous Nature**

This product is classified as: Hazardous according to the criteria of SWA.

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

SUSMP Classification: None allocated.

**ADG Classification: 2** 

UN Number: 1950, AEROSOLS







# **GHS Signal word: DANGER**

Flammable aerosols Category 1

Serious eye damage/eye irritation Category 2B

Specific Target Organ Toxicity - Single Exposure Category 3

Reproductive Toxicity Category 1

### **HAZARD STATEMENT:**

H222: Extremely flammable aerosol

H229: Pressurised container: may burst if heated.

AUH066: Repeated exposure may cause skin dryness or cracking.

H320: Causes eye irritation.

H336: May cause drowsiness or dizziness.

H360: May damage fertility or the unborn child.

## **PREVENTION**

P202: Do not handle until all safety precautions have been read and understood.

P210: Keep away from heat, sparks, open flames and hot surfaces. - No smoking.

P211: Do not spray on an open flame or other ignition source.

P233: Keep container tightly closed.

P240: Ground/bond container and receiving equipment.

P241: Use explosion-proof electrical ventilating, lighting and other equipment.

P242: Use only non-sparking tools.

P243: Take precautionary measures against static discharge.

P251: Do not pierce or burn, even after use.

P261: Avoid breathing fumes, mists, vapours or spray.

P262: Do not get in eyes, on skin, or on clothing.

P264: Wash contacted areas thoroughly after handling.

### SAFETY DATA SHEET

Issued by: Candan Industries Pty. Ltd

Telephone: (07) 3209 8733
In New Zealand: Phone 0212 811 500, Fax 09 929 3177



Page: 2 of 7

This version issued: July, 2025

P271: Use only outdoors or in a well ventilated area.

P280: Wear protective gloves, protective clothing and eye or face protection.

#### **RESPONSE**

P362: Take off contaminated clothing and wash before reuse.

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

P303+P361+P353: IF ON SKIN (or hair): Remove immediately all contaminated clothing. Rinse skin with water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: If exposed or concerned: Get medical advice.

P337+P313: If eye irritation persists: Get medical advice.

P372: Explosion risk in case of fire.

P381: Eliminate all ignition sources if safe to do so.

P370+P378: In case of fire, use carbon dioxide, dry chemical, foam, water fog. Water fog or fine spray is the preferred medium for large fires.

### **STORAGE**

P405: Store locked up.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P410+P412: Store below 30°C, protect from direct sunlight and do not expose to temperatures exceeding 50°C.

### **DISPOSAL**

P501: If they can not be recycled, dispose of contents to an approved waste disposal plant and containers to landfill (see Section 13 of this SDS).

## Statement of Hazardous Nature (New Zealand)

Aerosols (Flammable, Carcinogenic) Group Standard 2020 HSR002517

**DG Classification:** Classified as a Dangerous Good for transport in accordance with the Land Transport Rule Dangerous Goods 2005 and NZS 5433:2007.

## **Emergency Overview**

Physical Description & Colour: Dispensed product is a clear colourless liquid

Odour: Fragrant mint-like odour

**Major Health Hazards:** may impair fertility, may cause harm to unborn children, eye irritant, repeated exposure may cause skin dryness or cracking, vapours may cause drowsiness and dizziness.

Section 3 - Composition/Information on Ingredients				
Ingredients	CAS No	Conc, %	TWA (mg/m <sup>3</sup> )	STEL (mg/m³)
Alkanes, <sub>C3-4</sub>	68475-59-2	30-40	not set	not set
Acetone	67-64-1	<30	1185	2375
n-Propyl acetate	109-60-4	<15	835	1040
Toluene	108-88-3	<10	191	574
Isopropanol	67-63-0	<2.5	983	1230
n-Butanol	71-36-3	<2.5	152	Peak
Propan-1-ol	71-23-8	<1	492	614

This is a commercial product whose exact ratio of components may vary slightly. Minor quantities of other non hazardous ingredients are also possible.

The SWA TWA exposure value is the average airborne concentration of a particular substance when calculated over a normal 8 hour working day for a 5 day working week. The STEL (Short Term Exposure Limit) is an exposure value that may be equalled (but should not be exceeded) for no longer than 15 minutes and should not be repeated more than 4 times per day. There should be at least 60 minutes between successive exposures at the STEL. The term "peak "is used when the TWA limit, because of the rapid action of the substance, should never be exceeded, even briefly.

### Section 4 - First Aid Measures

## **General Information:**

You should call The Poisons Information Centre if you feel that you may have been poisoned, burned or irritated by this product. The number is 13 11 26 from anywhere in Australia (0800 764 766 in New Zealand) and is available at all times. Have this SDS with you when you call.

### **SAFETY DATA SHEET**

Issued by: Candan Industries Pty. Ltd

Telephone: (07) 3209 8733
In New Zealand: Phone 0212 811 500, Fax 09 929 3177



Page: 3 of 7

This version issued: July, 2025

**Inhalation:** No first aid measures normally required. However, if inhalation has occurred, and irritation has developed, remove to fresh air and observe until recovered. If irritation becomes painful or persists more than about 30 minutes, seek medical advice.

**Skin Contact:** Wash gently and thoroughly with water (use non-abrasive soap if necessary) for 5 minutes or until chemical is removed.

**Eye Contact:** Immediately flush the contaminated eye(s) with lukewarm, gently flowing water for 15 minutes or until the product is removed, while holding the eyelid(s) open. Take care not to rinse contaminated water into the unaffected eye or onto the face. Obtain medical attention immediately. Take special care if exposed person is wearing contact lenses.

**Ingestion:** If product is swallowed or gets in mouth, do NOT induce vomiting; wash mouth with water and give some water to drink. If symptoms develop, or if in doubt contact a Poisons Information Centre or a doctor.

# **Section 5 - Fire Fighting Measures**

**Fire and Explosion Hazards**: The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both), fire gases. There is little risk of an explosion from this product if commercial quantities are involved in a fire.

Fire decomposition products from this product may be toxic if inhaled. Take appropriate protective measures.

**Extinguishing Media:** Water fog or fine spray is the preferred medium for large fires. Try to contain spills, minimise spillage entering drains or water courses.

**Fire Fighting:** If a significant quantity of this product is involved in a fire, call the fire brigade. There is a danger of a violent reaction or explosion if significant quantities of this product are involved in a fire. Recommended personal protective equipment is full fire kit and breathing apparatus.

Flash point: -20°C
Upper Flammability Limit: 12.8%
Lower Flammability Limit: 2.5%
Autoignition temperature: No data.

Flammability Class: Flammable Category 2 (GHS); Highly Flammable (AS1940).

### Section 6 - Accidental Release Measures

**Accidental release:** This product is sold in small packages, and the accidental release from one of these is not usually a cause for concern. For minor spills, clean up, rinsing to sewer and put empty container in garbage. Although no special protective clothing is normally necessary because of occasional minor contact with this product, it is good practice to wear impermeable gloves when handling chemical products. In the event of a major spill, prevent spillage from entering drains or water courses and call emergency services.

# Section 7 - Handling and Storage

**Handling:** Keep exposure to this product to a minimum, and minimise the quantities kept in work areas. Check Section 8 of this SDS for details of personal protective measures, and make sure that those measures are followed. The measures detailed below under "Storage" should be followed during handling in order to minimise risks to persons using the product in the workplace. Also, avoid contact or contamination of product with incompatible materials listed in Section 10.

**Storage:** Store in a cool (below 30°C), well ventilated area. Protect from direct sunlight. Make sure that surrounding electrical devices and switches are suitable. Check containers and valves periodically for leaks. If you keep large quantities of Dangerous Goods, you may be required to license the premises or notify your Dangerous Goods authority. If you have any doubts, we suggest you contact your Dangerous Goods authority in order to clarify your obligations. Check packaging - there may be further storage instructions on the label.

## **Section 8 - Exposure Controls and Personal Protection**

The following Australian Standards will provide general advice regarding safety clothing and equipment:

Respiratory equipment: **AS/NZS 1715**, Protective Gloves: **AS 2161**, Occupational Protective Clothing: AS/NZS 4501 set 2008, Industrial Eye Protection: **AS1336** and **AS/NZS 1337**, Occupational Protective Footwear: **AS/NZS2210**.

SWA Exposure Limits	TWA (mg/m³)	STEL (mg/m³)
Acetone	1185	2375
n-Propyl acetate	835	1040
Toluene	191	574

### **SAFETY DATA SHEET**

Issued by: Candan Industries Pty. Ltd

Telephone: (07) 3209 8733
In New Zealand: Phone 0212 811 500, Fax 09 929 3177



Page: 4 of 7

This version issued: July, 2025

 Isopropanol
 983
 1230

 n-Butanol
 152
 Peak

 Propan-1-ol
 492
 614

No special equipment is usually needed when occasionally handling small quantities. The following instructions are for bulk handling or where regular exposure in an occupational setting occurs without proper containment systems.

**Ventilation:** This product should only be used in a well ventilated area. If natural ventilation is inadequate, use of a fan is suggested.

**Eye Protection:** Protective glasses or goggles should be worn when this product is being used. Failure to protect your eyes may cause them harm. Emergency eye wash facilities are also recommended in an area close to where this product is being used.

**Skin Protection:** You should avoid contact even with mild skin irritants. Therefore you should wear suitable impervious elbow-length gloves and facial protection when handling this product. See below for suitable material types.

**Protective Material Types:** We suggest that protective clothing be made from the following materials: Viton, nitrile, butyl rubber, Teflon, PE/EVAL, Responder, polyvinyl alcohol.

**Respirator:** Usually, no respirator is necessary when using this product. However, if you have any doubts consult the Australian Standard mentioned above. Otherwise, not normally necessary.

Eyebaths or eyewash stations should, if practical, be provided near to where this product is being handled commercially.

## **Section 9 - Physical and Chemical Properties:**

Physical Description & colour: Dispensed product is a clear colourless liquid

Odour: Fragrant mint-like odour

**Boiling Point:** Not available.

**Freezing/Melting Point:** No specific data. Liquid at normal temperatures.

Volatiles: No data.

Vapour Pressure: 23.76 kPa (dispensed product)

**Vapour Density:** No data. Specific Gravity: No data. Water Solubility: No data. pH: No data. Volatility: No data. **Odour Threshold:** No data. **Evaporation Rate:** No data. Coeff Oil/water Distribution: No data Autoignition temp: No data.

## Section 10 - Stability and Reactivity

**Reactivity:** This product is unlikely to react or decompose under normal storage conditions. However, if you have any doubts, contact the supplier for advice on shelf life properties.

**Conditions to Avoid:** Store below 30°C, protect from direct sunlight and do not expose to temperatures exceeding 50°C. Keep containers and surrounding areas well ventilated. Keep away from sources of sparks or ignition. Any electrical equipment in the area of this product should be flame proofed.

**Incompatibilities:** strong oxidising agents, chemically active metals such as lithium, beryllium and barium, sodium hydroxide and potash.

**Fire Decomposition:** Combustion forms carbon dioxide, and if incomplete, carbon monoxide and possibly smoke. Water is also formed. Carbon monoxide poisoning produces headache, weakness, nausea, dizziness, confusion, dimness of vision, disturbance of judgment, and unconsciousness followed by coma and death.

**Polymerisation:** This product will not undergo polymerisation reactions.

## **Section 11 - Toxicological Information**

**Local Effects:** 

**Target Organs:** There is no data to hand indicating any particular target organs.

Toluene is a SWA Class 3 Reproductive risk.

### SAFETY DATA SHEET

Issued by: Candan Industries Pty. Ltd

Telephone: (07) 3209 8733
In New Zealand: Phone 0212 811 500, Fax 09 929 3177



Page: 5 of 7

This version issued: July, 2025

# **Classification of Hazardous Ingredients**

### Ingredient

### Alkanes, C<sub>3-4</sub>

- · Gases under pressure
- Flammable gas category 1
- Acute toxicity category 2
- Carcinogenicity category 1A
- Germ cell mutagenicity category 1B
- Eye irritation category 2A
- Skin irritation category 2
- Specific target organ toxicity (single exposure) category 3
- Specific target organ toxicity (repeated exposure) category 1
- Reproductive toxicity category 1B

### Acetone

- Flammable liquid category 2
- Eye irritation category 2A
- Specific target organ toxicity (single exposure) category 3

### N-propyl Acetate

- Flammable liquid category 2
- Specific target organ toxicity (single exposure) category 3
- Eye irritation category 2A

#### Toluene

- Flammable liquid category 2
- Skin irritation category 2
- Specific target organ toxicity (repeated exposure) category 2
- Reproductive toxicity category 1A
- Specific target organ toxicity (single exposure) category 3
- Aspiration hazard category 1

### Isopropanol

- Flammable liquid category 2
- Eye irritation category 2A
- Specific target organ toxicity (single exposure) category 3

### N-butanol

- Flammable liquid category 3
- Acute toxicity category 4
- Specific target organ toxicity (single exposure) category 3
- Skin irritation category 2
- Specific target organ toxicity (single exposure) category 3
- Eye damage category 1

## **Potential Health Effects**

### Inhalation:

**Short Term Exposure:** High vapour pressures may cause drowsiness and dizziness. In addition product may be mildly irritating, although unlikely to cause anything more than mild transient discomfort. Intentional misuse by deliberately concentrating and inhaling contents of aerosol containers can be harmful or fatal.

**Long Term Exposure:** Vapours may cause drowsiness and dizziness.

### **Skin Contact:**

**Short Term Exposure:** Major health effect from this product is misuse of the aerosol function. If sprayed continuously on skin or in eyes, it can cause frostbite.

### **SAFETY DATA SHEET**

Issued by: Candan Industries Pty. Ltd

Telephone: (07) 3209 8733
In New Zealand: Emergency 0212 811 500
In New Zealand: Phone 0212 811 500, Fax 09 929 3177



Page: 6 of 7

This version issued: July, 2025

Long Term Exposure: Repeated exposure may cause skin dryness or cracking.

Eye Contact:

**Short Term Exposure:** If sprayed directly in the eye, this product will irritate. If spraying is prolonged, it may cause

damage through frostbite.

Long Term Exposure: No data for health effects associated with long term eye exposure.

Ingestion:

Short Term Exposure: Significant oral exposure is considered to be unlikely. However, this product may be

irritating to mucous membranes but is unlikely to cause anything more than transient discomfort.

**Long Term Exposure**: No data for health effects associated with long term ingestion.

Carcinogen Status:

**SWA:** No significant ingredient is classified as carcinogenic by SWA. **NTP:** No significant ingredient is classified as carcinogenic by NTP.

**IARC:** Toluene is Class 3 - unclassifiable as to carcinogenicity to humans. Isopropanol is Class 3 - unclassifiable as to carcinogenicity to humans.

See the IARC website for further details. A web address has not been provided as addresses frequently change.

# **Section 12 - Ecological Information**

Insufficient data to be sure of status.

# **Section 13 - Disposal Considerations**

**Disposal:** Aerosol containers can be disposed of in household waste or, in some areas, recycled, when empty. If it is necessary to dispose of unused product, or containers which are not empty, a specialist waste disposal company should be used. Never crush, puncture or burn aerosol containers, even when empty.

# **Section 14 - Transport Information**

Dangerous according to Australian Dangerous Goods (ADG) Code, IATA and IMDG/IMSBC criteria.

UN Number: 1950, AEROSOLS

**Hazchem Code: 2YE** 

Special Provisions: 63, 190, 277, 327, 344, 381

Limited quantities: ADG 7 specifies a Limited Quantity value of 1000mL for this class of product.

Dangerous Goods Class: Class 2.1: Flammable gases.

Packing Group: Not set

Packing Instruction: P207, LP200

Class 2.1 Flammable gases shall not be loaded in the same vehicle or packed in the same freight container with Classes 1 (Explosives), 3 (Flammable Liquids) (where both flammable liquids and flammable gases are in bulk), 4.1 (Flammable Solids), 4.2 (Spontaneously Combustible Substances), 4.3 (Dangerous When Wet Substances), 5.1 (Oxidising Agents), 5.2 (Organic Peroxides), and 7 (Radioactive Substances). They may however be loaded in the same vehicle or packed in the same freight container with Classes 2.2 (Non-flammable Non-Toxic gases), 3 (Flammable liquids except where both flammable liquids and flammable gases are in bulk), 6 (Toxic Substances), 8 (Corrosive Substances) 9 (Miscellaneous dangerous goods), Foodstuffs and foodstuff empties.

## **Section 15 - Regulatory Information**

AICS: All of the significant ingredients in this formulation are compliant with NICNAS regulations.

The following ingredients: Acetone, Toluene, are mentioned in the SUSMP.

**New Zealand:** 

Aerosols (Flammable, Carcinogenic) Group Standard 2020 HSR002517

### Section 16 - Other Information

This SDS contains only safety-related information. For other data see product literature.

Acronyms:

**ADG Code** Australian Code for the Transport of Dangerous Goods by Road and Rail (7<sup>th</sup> edition)

AICS Australian Inventory of Chemical Substances

### **SAFETY DATA SHEET**

Issued by: Candan Industries Pty. Ltd

Telephone: (07) 3209 8733
In New Zealand: Phone 0212 811 500, Fax 09 929 3177



Page: 7 of 7

This version issued: July, 2025

SWA Safe Work Australia, formerly ASCC and NOHSC CAS number Chemical Abstracts Service Registry Number

Hazchem Code Emergency action code of numbers and letters that provide information to emergency

services especially firefighters

IARC International Agency for Research on Cancer

NOS Not otherwise specified

NTP National Toxicology Program (USA)

SUSMP Standard for the Uniform Scheduling of Medicines & Poisons

**UN Number** United Nations Number

THIS SDS SUMMARISES OUR BEST KNOWLEDGE OF THE HEALTH AND SAFETY HAZARD INFORMATION OF THE PRODUCT AND HOW TO SAFELY HANDLE AND USE THE PRODUCT IN THE WORKPLACE. EACH USER MUST REVIEW THIS SDS IN THE CONTEXT OF HOW THE PRODUCT WILL BE HANDLED AND USED IN THE WORKPLACE.

IF CLARIFICATION OR FURTHER INFORMATION IS NEEDED TO ENSURE THAT AN APPROPRIATE RISK ASSESSMENT CAN BE MADE, THE USER SHOULD CONTACT THIS COMPANY SO WE CAN ATTEMPT TO OBTAIN ADDITIONAL INFORMATION FROM OUR SUPPLIERS OUR RESPONSIBILITY FOR PRODUCTS SOLD IS SUBJECT TO OUR STANDARD TERMS AND CONDITIONS, A COPY OF WHICH IS SENT TO OUR CUSTOMERS AND IS ALSO AVAILABLE ON REQUEST.

Please read all labels carefully before using product.

## Australia:

This SDS is prepared in accord with the SWA document "Preparation of Safety Data Sheets for Hazardous Chemicals - Code of Practice" (Feb 2016)

### **New Zealand**

HSNO Approved Code of Practice: Preparation of Safety Data Sheets. New Zealand Chemical Industry Council September 2006.

Revision Issued: July 2025 – update to emergency contact

### **SAFETY DATA SHEET**

Issued by: Candan Industries Pty. Ltd

Telephone: (07) 3209 8733
In New Zealand: Emergency 0212 811 500
In New Zealand: Phone 0212 811 500, Fax 09 929 3177